

FEATURES

- Medium Flow
- Heat Resistance
- Mechanical Resistance
- Free of zinc and oil additives
- FDA Rating: 21 CFR 177.1640

APPLICATIONS

- XPS insulation
- Extrusion
- Injection Molding

PROPERTIES

| Physical | English | Value | Metric | Value | Test Method |
|---------------------------------|--------------------|--------------------|-------------------|--------------------|-------------|
| Melt Flow Rate (200°C/5.0 Kg) | g/10 min | 2.6 | g/10 min | 2.6 | ASTM D1238 |
| Density | lb/ft ³ | 65 | g/cm ³ | 1.04 | ASTM D792 |
| Mechanical | | | | | |
| Break Elongation | % | 5 | % | 5 | ASTM D638 |
| Tensile Modulus | Kpsi | 520 | MPa | 3,580 | ASTM D638 |
| Thermal | | | | | |
| Vicat Temperature | °F | 216 | °C | 102 | ASTM D1525 |
| HDT @ 264 psi (unannealed) | °F | 198 | °C | 92 | ASTM D648 |
| Ignition Characteristics | | | | | |
| Flammability | - | HB | - | HB | UL 94 |
| Optical | | | | | |
| Light Transmittance | % | 90 | % | 90 | ASTM D1003 |

Properties reported in this data sheet are determined according to referred standard methods. Values shown represent averages from typical results measured in the laboratory and are provided only as a guide, not as specification limits.

EXTRUSION CONDITIONS

| | °C | °F |
|------------------|---------|---------|
| Initial zone | 40 | 104 |
| Feeding zone | 180-190 | 356-374 |
| Transport zone | 190-200 | 374-392 |
| Compression zone | 200-210 | 392-410 |
| Pumping zone | 210-220 | 410-428 |
| Melt | 250 | 482 |

ADDITIONAL INFORMATION
Warning:

Combustion of this material may cause hazardous fumes and gases that may be dangerous to health, especially in enclosed places. It should be noted that excessive heating or long residence time may cause degradation or yellowing.

Note:

The data contained herein is provided for information purposes only. By providing such information, Resirene S.A de C.V. makes no guarantee and does not assume any liability with respect to the accuracy or completeness of such information and the results obtained with this product in any specific instance; and hereby expressly disclaims all implied warranties of merchantability or fitness to a particular purpose. Nothing contained herein shall be construed as a license to use the products of Resirene, S.A. de C.V in any manner that would infringe any patent.